

◆ 產品規格 / PRODUCTS SPECIFICATIONS

厚度 (mm)	寬×長 (mm)	色相 Color
0.5	915 × 1830 (3' × 6')	透明 CLEAR
0.8		
1.0		
1.2	1M × 2M	
1.5	1220 × 2440 (4' × 8')	
1.8		
2.0		

◆ 物性表 / PHYSICAL PROPERTIES

項目 Test Items	試驗方法 Test Methods	單位 Units	試驗值 Test Value
比重 Specific Gravity	ASTM D-792	----	1.350
抗拉強度 Tensile Strength (MD)	ASTM D-638	kg/cm ²	550 ↑
抗拉強度 Tensile Strength (CD)	ASTM D-638	kg/cm ²	520 ↑
伸長率 Elongation at Yield	ASTM D-638 at 50 mm/min	%	100 ↑
拉伸彈性係數 Modulus of elasticity	ASTM 638	kg/cm ²	13000
彎曲強度 Flexural strength	ASTM D790	kg/cm ²	880
彎曲彈性係數 Flexural modulus	ASTM D790	kg/cm ²	20000
熱變形溫度 Heat deflection temperature	ASTM D648	°C	65.5
IZOD 耐衝擊強度 Impact strength(+20°C)	ASTM D256	kg.cm/cm ²	4.3
透光度 Light transmission(1 mm)	ASTM D1003	%	87

註：上述資料係試驗值，僅供客戶選擇參考，非品質標準亦不作任何商業證明使用。

Notes: The above data are test values for reference only not quality standards, not served as any commercial certification.